




**UP TO ϕ 100mm
AVAILABLE**



Sapphire Crystal (Al_2O_3)

As the hardest one of all the oxide crystals, Sapphire has the combination of optical and physical properties that makes it the best choice for a variety of demanding applications. Sapphire maintains its strength even at high temperature. It has good thermal properties, excellent electrical and dielectric properties and is resistant to chemical attack. These properties encourage the use of Sapphire in aggressive environments where long-term reliability, high optical transmission or good strength is required. Two methods are used in growth of sapphire crystal: Directional Temperature Gradient Technique (TGT) and Czochralski for the highest optical and substrate quality.

TGT Sapphire Characteristics

- High transparency from the vacuum ultraviolet (VUV) through the visible, near infra-red (NIR). Absorption of 35 ~ 65ppm/cm at $\lambda=1.06\mu\text{m}$.
- High optical homogeneity up to $\Delta n=5 \times 10^{-6}$ at 632nm.
- High structural quality: X-ray rocking curve FWHM=10", dislocation density: $10^3 \sim 10^4/\text{cm}^2$.
- Low dn/dt over a wide range of wavelengths.

Basic Properties

Crystal Structure:	Hexagonal System
Lattice:	$a=4.785\text{\AA}$, $c=12.991\text{\AA}$
Density:	3.98g/cm^3
Transmission Range:	150nm ~ 5500nm
Melting Point:	2042°C
Specific Heat:	0.418W·s/g/k
Thermal Conductivity:	25.12W/m/k (at 100°C)
Thermal Shock Resistance:	790W/m
Thermal Expansion Coefficient:	$5.8 \times 10^{-6}/\text{K}$
dn/dt (@633nm)	$13 \times 10^{-6}/\text{K}$
Mohs Hardness:	9
Refractive Index(n_o):	1.83 @ 260nm; 1.76 @ 630nm; 1.58 @ 5570nm

Main Applications

1. Applications in Microelectronics

Sapphire substrate with different orientations has different applications:

- (0 0 0 1) Basal Plane Sapphire Substrate:
Epitaxial Gallium Nitride chip for blue LED
IR detector
- (-1 1 0 2) R-Plane Sapphire Substrate:
GaAs wafer carriers
Microwave IC
SOS (Silicon on Sapphire)- High Speed IC
Pressure Transducer
- (1 -1 2 0) A Plane Sapphire Substrate:
The growth of high Tc superconductors

2. Application in Aerospace

Windows for sensors
Infrared countermeasure lamps

3. Application in Scientific Analysis

Very high pressure applications in replacement of glass or quartz tubes in NMR
Quartz replacement to improving durability and reducing contamination in mass spectroscopy

4. Application in Medical Area

Surgical tips
Endoscope lenses

5. Application in Optics

Illumination windows
Sapphire light guides
LCD projector windows
Optical components such as lenses, prisms and other laser and infrared optics

Quartz and other glass substrates/wafers/optics, and various crystal products are available. Contact us for more information!

PHOTONIK hv

PHOTONIK (SINGAPORE) PTE LTD

Tel: +65-6316-6370, +65-6316-2142 Fax: +65-6316-1082

Email: sales@photonik.com.sg Web: www.photonik.com.sg

Address: 8 Boon Lay Way, TradeHub 21, #04-04, Singapore 609964



Sapphire Crystal (Al₂O₃)

Selections of Sapphire Products

**UP TO ϕ 100mm
AVAILABLE**

Sapphire Substrate

Standard Specifications - Epi-Ready

Diameter	50.8 ± 0.05mm	76.2 ± 0.05mm
Thickness	330-430 ± 50µm C (0001) ± 0.2°	380-480 ± 50µm C (0001) ± 0.2°
Orientation	A (1120) ± 0.2° R (1102) ± 0.2°	A (1120) ± 0.2° R (1102) ± 0.2°
TTV and Bow	<20µm; or on request	<25µm; or on request
Front Surface	Epi polished	Epi polished
Back Side	Lapped or polished	Lapped or polished
Flatness	<5µm, or on request	<5µm, or on request
Roughness (Ra)	<0.5nm, or on request	<0.8nm, or on request
ORF	16.0 ± 1.0mm	22.0 ± 1.0mm
Primary Flat Location	A or M ± 0.5°	A or M ± 0.5°
Secondary Flat Location	90° to primary	90° to primary
Package	25-wafer cassette, or on request	25-wafer cassette, or on request

Note: Above shown are typical specs for reference. Users may specify application areas for confirmation of specs first.

Sapphire Windows & Mirrors

Standard Specifications

Diameter Tolerance	+ 0.00, - 0.10mm
Thickness Tolerance	± 0.02mm
Crystal Cut Orientation	c-axis ± 0.5°, or any other orientation per customers' request
Flatness	better than λ per 10mm (@633nm)
Parallelism	better than 20"
Surface Quality	30-20 scratch and dig per MIL-O-13830A; or per customer specially specified.
Bevel Processing	0.05mm
Wavefront Distortion	< $\lambda/2$ per inch (λ @ 1064nm)

Custom Sapphire Disc/Washer/Wafer & Optics

Special high precision sapphire windows, and other AR or HR coated sapphire optics are available upon request. Sapphire boule grown by CZ and TGT method and cut sapphire blocks is also available.

Quartz and other glass substrates/wafers/optics, and various crystal products are available. Contact us for more information!

PHOTONIK hv

PHOTONIK (SINGAPORE) PTE LTD

Tel: +65-6316-6370, +65-6316-2142 Fax: +65-6316-1082

Email: sales@photonik.com.sg Web: www.photonik.com.sg

Address: 8 Boon Lay Way, TradeHub 21, #04-04, Singapore 609964