



**VCM** Ranging from  $\text{Ø}1\text{mm}$  to  $\text{Ø}10\text{mm}$   
10.7mm from front to back  
For positioning of short, small diameter cylindrical components (Grin Lenses)  
Close access to both ends of the fastened objects  
A nylon tipped set screw housed in an adjustable height arm is for fixing use



**VCS** Ranging from  $\text{Ø}0.5\text{mm}$  to  $\text{Ø}20\text{mm}$   
For positioning of small cylindrical objects (Fiber Collimation Packages)  
A Clamping Arm (A brass locking thumbscrew and rubber landing pad) is for fixing use



**VCL** Ranging from  $\text{Ø}15\text{mm}$  to  $\text{Ø}50\text{mm}$   
For positioning of large cylindrical objects (Tube Lasers)  
A Clamping Arm (A brass locking thumbscrew and rubber landing pad) is for fixing use



**VCB** Ranging from  $\text{Ø}15\text{mm}$  to  $\text{Ø}90\text{mm}$   
For positioning of optical components, optomechanical structures  
A fastening screw provides locking force to the optic

## Contact Information:

**PHOTONIK (SINGAPORE) PTE LTD**

8 Boon Lay Way, TradeHub 21, #04-04, Singapore 609964  
Tel: +65-6316-6370, +65-6316-2142 Fax: +65-6316-1082  
Email: sales@photonik.com.sg Web: www.photonik.com.sg

## Local Representative:

